
Gea Cob

8 references · 2 versions · Recessed LED ground uplight

A compact ø125 mm recessed LED ground uplight with a head that tilts ±15° and turns 360°, for trees, plants and paths.





Shown: ø125 mm

TECHNICAL DATA

Light source:	LED
Power:	10.1 - 10.5 W
Lumen output:	869 - 1073 lm
Efficacy:	82.8 - 106.2 lm/W
Colour temperature:	2700K / 3000K / 4000K
CRI:	80
Beam angle:	17° / 53° (2 reflectors; ø125 mm Aluminium: 17°)
Dimming:	On-Off, DALI/PUSH
IP rating:	IP66-IP67 / IP65-IP67
UGR:	≤10
Dimensions:	Ø125 × 133 mm
Material:	Stainless steel AISI 316 and aluminium, tempered glass diffuser (ø125 mm Aluminium: glass diffuser)
Voltage:	100-240V / 50-60Hz; 220-240V / 50-60Hz
Insulation class:	I
Lifespan:	50,000 h L80B20
Warranty:	5 years (ø125 mm Aluminium: 2 years)
Also:	IK10, suitable for vehicle traffic; 2 reflectors (17° / 53°), honeycomb panel and asymmetric filter included (ø125 mm)

VERSIONS

Version	Dimensions	Power	Light output	CCT	Beam angle	Refs
ø125 mm Aluminium	Ø125 × 133 mm	10.5 W	869 - 934 lm	2700K / 4000K	17°	2
ø125 mm	Ø125 × 133 mm	10.1 W	914 - 1073 lm	2700K / 3000K / 4000K	17° / 53°	6

Every reference is listed with its own values on the product page.

Compacte inbouw LED-grondspot van ø125 mm met een kop die ±15° kantelt en 360° draait, voor bomen, planten en paden.

Encastré de sol LED compact de ø125 mm à tête inclinable de ±15° et orientable sur 360°, pour les arbres, les plantes et les allées.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.