
Selentis Round

6042.270.15.5 / 6042.270.34.5 · 2 references · Alabaster LED wall light, round

Selentis Round: a round alabaster disc that glows warmly from within, with a 2700K LED and an included phase-cut dimmable driver.





TECHNICAL DATA

Power:	8 - 20 W
Lumen output:	550 - 1330 lm
Efficacy:	66.5 - 68.8 lm/W
Dimensions:	Ø150 × 60 mm / Ø340 × 71 mm
Light source:	Bridgelux SMD2835 LED
Colour temperature:	2700K
CRI:	>90
UGR:	<19
IP rating:	IP20
Dimming:	Phase cut (driver included); DALI with separate driver
Material:	Natural alabaster (gypsum) diffuser, die-cast aluminium base in RAL 8022 brown/black
Mounting:	Wall mounted on the supplied mounting plate
Lifespan:	approx. 50,000 h
Warranty:	5 years (with the recommended driver)
Driver:	Phase-cut dimmable driver included; DALI driver art. 0110.200.40.0 (200 mA, 8 W) / 0120.500.40.1 (500 mA, 20 W)
Also:	Each piece of natural alabaster is uniquely veined; Europlug power cable 2000 mm art. 0502.075.20.0 available

VERSIONS

Reference	Dimensions	Power	Light output	Efficacy	DALI driver (optional)
6042.270.15.5	Ø150 × 60 mm	8 W	550 lm	68.8 lm/W	0110.200.40.0 (200 mA, 8 W)
6042.270.34.5	Ø340 × 71 mm	20 W	1330 lm	66.5 lm/W	0120.500.40.1 (500 mA, 20 W)

Colour: natural alabaster, base RAL 8022 brown/black. REFERENCES: 2 refs, listed per version on the product page.

Selentis Round: een ronde schijf van albast dat warm van binnenuit gloeit, met een LED van 2700K en een inbegrepen dimbare fase-aansnijdingsdriver.

Selentis Round : un disque rond en albâtre qui rayonne chaleureusement de l'intérieur, avec LED 2700K et driver gradable à coupure de phase inclus.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.