

Spotti Surface LED Spotlight


10W surface-mounted LED spotlight with Bridgelux light source, delivering up to 750 lm, CRI >90, and multiple beam angles (15°–45°) with flexible dimming options.

PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux V10B or DtW
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including phase cut dimmable driver
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	▲ 24°
ADJUSTABLE	No
DIMMABLE	Yes
SIZE	Ø72 X 110mm



OPTIONS

OPTIONAL BEAM ANGLE	▲ 15°	Art. no.: 3067.010.15.0
	▲ 36°	Art. no.: 3067.010.36.0
	▲ 45°	Art. no.: 3067.010.45.0
ANTI-GLARERING	Black	Included
	Gold	Art. no.: 3067.030.00.9
HONEYCOMB	Art. no.: 3067.040.00.0	
DRIVER OPTIONS	1/10V	250mA 1-11W Art. no.: 0111.250.30.0 This driver can only be placed externally
	DALI	250mA 6-13W Art. no.: 0114.250.40.1 This driver can only be placed externally



INFORMATION

! Full warranty only applies when fixture is purchased in combination with recommended driver.

ANTI-GLARERING



HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5200.270.24.Δ	V10B	Bridgelux	700lm	10W	70lm/W	2700K	>90	50.000 Hrs	250mA
5200.300.24.Δ	V10B	Bridgelux	750lm	10W	75lm/W	3000K	>90	50.000 Hrs	250mA
5200.125.24.Δ	DtW	Bridgelux	750lm	10W	75lm/W	1800-3000K	>90	50.000 Hrs	250mA

Δ See colors

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be