

ATIA P/P

This surface-mounted fixture integrates a 40W/50W LED, delivering 2100–2800 lumens at 3000K. With a 260-degree diffused beam, IP20 protection, and phase-cut dimmability, it offers a refined, high-performance lighting solution for modern spaces.



ATIA P/P

FATPB1-BIANCO-WHITE

TECHNICAL DATA


Installation: Interno _ Lampada a soffitto
Source: Led Integrato
Power: 40W
Power Supply: 220-240V AC _ 50/60Hz
Dimming: Dimmerabile _ taglio fase+push non incl.
Lumen: 2100lm
Color Temperature: 3000K
Light Beam: 260° _ Diffusa
CRI: >80
Lifespan: 30.000h
IP Rating: IP20
Insulation Class: I
Gross Weight: 4.00 Kg
Net Weight: 2.80 Kg

Montatura in alluminio satinato bianco. Diffusore in silicone bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi).

White satin-finish aluminium mount. White opal silicone diffuser. Phase cut dimmable LED light source via external dimmer + push (not included).

Monture en aluminium blanc satiné . Diffuseur en silicone opale blanc. Source lumineuse LED à gradation progressive via un gradateur externe+poussoir (pas inclus).

Weißer satiniertes Aluminiumrahmen. Weißer opaler Silikondiffusor. Phase-Cut dimmbare LED-Lichtquelle über externen Dimmer+Push (nicht enthalten).



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

ATIA P/P

This surface-mounted fixture integrates a 40W/50W LED, delivering 2100–2800 lumens at 3000K. With a 260-degree diffused beam, IP20 protection, and phase-cut dimmability, it offers a refined, high-performance lighting solution for modern spaces.



ATIA P/P

FATPN1-NERO-BLACK

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led Integrato

Power: 40W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 1900lm

Color Temperature: 3000K

Light Beam: 260° _ Diffusa

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Gross Weight: 4.00 Kg


Net Weight: 2.80 Kg

Montatura in alluminio satinato nero. Diffusore in silicone bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi).

Black satin finish aluminium mount. White opal silicone diffuser. Phase cut dimmable LED light source via external dimmer + push (not included).

Monture en aluminium noir satiné. Diffuseur en silicone blanc opale. Source lumineuse LED à gradation progressive via un gradateur externe+poussoir (pas inclus).

Schwarzer satiniertes Aluminiumrahmen. Opal Weißer Silikon Diffusor. Phase-Cut dimmbare LED-Lichtquelle über externen Dimmer+Push (nicht enthalten).



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be