

Air Max


Premium die-cast aluminium spotlight featuring a Bridgelux V8 LED (550lm, 6.2W) with a 50,000-hour lifetime. Offers 0–60° tilt, 360° rotation, IP20 rating, and customizable anti-glare rings, glass, or honeycomb louvers.

PRODUCT MATERIAL	Die-cast Aluminium
LIGHT SOURCE	Bridgelux V8 Array
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Excluding driver, SELECT OPTION
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	 23°
ADJUSTABLE	Yes – 0–60° – 360°
SIZE	Ø40 X 70mm




OPTIONS


OPTIONAL BEAM ANGLE		Art. no.: 4912.010.26.0
		Art. no.: 4912.010.36.0
ANTI-GLARE RING	Black	Included
	White	Art. no.: 4912.922.99.3
	Gold	Art. no.: 4912.922.99.9
GLASS	Prismatic	Art. no.: 4912.933.94.0
	Frosted	Art. no.: 4912.933.90.0
	Striped	Art. no.: 4912.933.96.0
HONEYCOMB	Art. no.: 4912.933.91.0	
DRIVER OPTIONS	On/off	350mA 6–10W Art. no.: 0110.350.10.3
	Phase cut	350mA 1–7W Art. no.: 0107.350.20.2
	DALI	350mA 3–18W Art. no.: 0118.350.40.0 Max. 2 fixtures connected in serie per driver
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0	
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0	
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0	



Hole size



Technical drawing



Versatile usage

ANTI-GLARE RING



Black

White

Gold

GLASS



Striped

Frosted

Prismatic

HONEYCOMB



Honeycomb

INFORMATION

Always select a driver option and add the selected driver to your order.



Full warranty only applies when fixture is purchased in combination with recommended driver.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be