



MAC WALL

12W outdoor LED bollard with 890-900lm output, 100° beam angle, IP65 protection, IK06 impact resistance, CRI >80, and aluminium-polycarbonate construction for landscape lighting.

Mac f loor



Mac f loor XL



Technical Information

Power	12W	12W
Installation	Floor	Floor
Color	3.000K / 4.000K	3.000K / 4.000K
Temperature	890 lm / 900 lm	890 lm / 900 lm
Lumens	Aluminium and Polycarbonate	Aluminium and Polycarbonate
Material	White / Black / Corten	White / Black / Corten
Finishes		

Code	○ 3.000 483	○ 3.000 4843
	☾ K 7	☾ K 4844
	☾ 4.000 483	☾ 4.000 4845
	☾ K 8	☾ K 4846
	☾ 3.000 483	☾ 3.000 4847
	● K 9	● K 4848
	4.000 484	4.000
	K 0 	K 
	3.000 484	3.000

Accessories



Linear Joint IP68
Ø26x95mm

■ 5671 New




T Joint IP68
74x118mm

■ 5672 New



X Joint IP68
122x122mm

■ 5673 New



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be