



Spotti

Surface-mounted LED spotlight featuring 14W power, 1205lm output, 40° beam angle, CRI 97+, TRIAC dimming, switchable 2700K-4000K CCT, 355° rotation, and 90° tilt for precise lighting control.

Mini Concord surface


Concord surface



Technical Information

Power	7W	14W
Installation	Surface	Surface
Color	Switch 2.700K / 3.200K / 4.000K	Switch 2.700K / 3.200K / 4.000K
Temperature	850 lm	1.205 lm
Lumens	Aluminium	Aluminium
Material	White / Black	White / Black
Finishes		

Code	○ 4334-N	○ 5071
	● 4335-N	● 5072
	○ Custom	○ Custom
	RAL	RAL
	CRI ≥80	CRI ≥97
	1/30	1/4/12



○ Consult delivery terms and conditions.

3 YEARS | 30.000 HOURS | IP 20 | 220/240 VAC | PF >0,9 | -40° | 50/60 Hz | +40°C / -10°C | TRIAC DIMM | CCT SWITCH

beneito-faure.com

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be