


OCULUM 3PH

Three-phase LED track spotlight with adjustable positioning, CRI >90, UGR<19, interchangeable optics, IP20 protection, and high-performance illumination for professional accent and display lighting.

Oculum 3PH



Technical Information

Power	15W / 25W
Lumens	1.628 lm - 2.625 lm
Installation	Three Phase Track
Material	Aluminium
Finishes	White (9003) / Black (9005)

Code	Di user (Angle)	Power	CCT (Lm)	Driver	Colour
Code 7	Narrow (15°) N	15W 8	2.700K (95 lm/W) 2	On/O 1	○ White 1
	Spot (22°) S	25W 9	3.000K (100 lm/W) 3	Triac 4	● Black 2
	Medium (36°) M		4.000K (105 lm/W) 4		
	Elliptic (30°-60°) E				

Code: **7** **6**

*Create your code according to your preferences.

Consult delivery terms and conditions.

Accessories



Honeycomb Snoot anti-glare

● 20811



Oval di user

● 20833




Snoot

● 20855



Wallwasher

● 20877



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be