

Play Snoot

Recessed LED downlight with adjustable focal point, CRI 92, IP54 protection, DALI control, 230V operation, 34° medium beam angle, and up to 1382lm output.


Play Snoot Mini Round Adjustable

LedsC4 Team

Recessed ceiling lights Play Snoot Mini Round Adjustable LED 4.4W 2700K CRI 80 28.8° DALI-2/PUSH Black IP54 309lm

Technical features

Luminaire total power: 4.4W
Real lumens: 340
Real lm/W: 77
Correlated Colour Temperature (CCT): 2700K
Lens / reflector angle: MEDIUM 28°
UGR: <=16
Structure material: Aluminium
Structure finish: Black
Diffuser material: Methacrylate
Diffuser finish: Transparent
Driver Brand: OSRAM
Voltage / frequency: 220-240V/50-60Hz
Dimming protocol: DALI-2/PUSH
Power Factor: 0.89
Useful life: 50,000h L80B20
Warranty: 2 years
Easily recyclable luminaire



Luminotechnic features

Luminance C90°G65°: 2986
CRI: 80
MacAdam steps: 2
Photobiological risk: RG1

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	13.4
UGR lengthwise	13.6

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	3W	2700K



Logistics



Net weight (kg): 0.16

Packaged weight (kg): 0.25

Packaging: 170mmx120mm x 120mm



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

Play Snoot

Recessed LED downlight with adjustable focal point, CRI 92, IP54 protection, DALI control, 230V operation, 34° medium beam angle, and up to 1382lm output.

Play Mini Snoot Round Adjustable

Recessed ceiling lights Play Mini Snoot Round Adjustable LED 8.5W 2700K CRI 92 52° ON-OFF White IN IP20 / OUT IP54 729lm

Technical features

Luminaire total power: 8.5W
Real lumens: 802
Real lm/W: 94
Correlated Colour Temperature (CCT): 2700K
Lens / reflector angle: FLOOD 52°
UGR: <=22
Structure material: Aluminium
Structure finish: White
Diffuser material: Methacrylate
Diffuser finish: Transparent
Driver Brand: VOSSLOH-SCHWABE
Voltage / frequency: 100-240V ~ 50/60Hz
Dimming protocol: ON-OFF
Useful life: 50,000h L80B20
Warranty: 5 years
Easily recyclable luminaire





Luminotechnic features

Luminance C0°G65°: 282
Luminance C90°G65°: 282
CRI: 92
MacAdam steps: 2
Photobiological risk: RG2

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	19.6
UGR lengthwise	19.6

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	8.5W	2700K



Logistics



Net weight (kg): 0.17
Packaged weight (kg): 0.23
Packaging: 160mmx105mm x 105mm

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be