

Spotti

Engineered with Bridgelux LEDs, this 10W luminaire delivers up to 750 lumens with a high CRI (>90). It features versatile beam angles, robust dimming integration, and an anti-glare design.

PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux V10B or DtW
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including phase cut dimmable driver
COLORS (Δ)	○ 3 = RAL 9003 ● white 5 = RAL 9005 black
BEAM ANGLE	24°
ADJUSTABLE	No
DIMMABLE	Yes
SIZE	Ø72 X 110mm




OPTIONS

OPTIONAL BEAM ANGLE	15°	Art. no.: 3067.010.15.0
	36°	Art. no.: 3067.010.36.0
	45°	Art. no.: 3067.010.45.0
ANTI-GLARE RING	Black	Included
	Gold	Art. no.: 3067.030.00.9
HONEYCOMB		Art. no.: 3067.040.00.0
DRIVER OPTIONS	1/10V	250mA 1-11W Art. no.: 0111.250.30.0 This driver can only be placed externally
	DALI	250mA 6-13W Art. no.: 0114.250.40.1 This driver can only be placed externally

INFORMATION

⚠ Full warranty only applies when fixture is purchased in combination with recommended driver.



ANTI-GLARE RING



HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5200.270.24.Δ	V10B	Bridgelux	700lm	10W	70lm/W	2700K	>90	50.000 Hrs	250mA
5200.300.24.Δ	V10B	x	750lm	10W	75lm/W	3000K	>90	50.000 Hrs	250mA
5200.125.24.Δ	DtW	Bridgelux	750lm	10W	75lm/W	1800-3000K	>90	50.000 Hrs	250mA

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be