


URBAN

Operating at 230VAC, this IP40 linear LED system delivers up to 136 lm/W with >95 CRI and UGR<19. It supports 46W-103W outputs, multiple CCTs, and Casambi/DALI dimming integrations.



Control accessories pages 282-289.

Technical Information

Power	46W / 57W / 69W / 80W / 103W
Lumens	5.152 lm - 14.008 lm
Installation	Surface / Pendant
Material	Aluminium
PCB	Rigid

Code	Di user (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code 6	UGR (78°) 4	1.130m 3	2.700K (112 lm/W) - 40W/m 2	On / O 1	☐ White (9003) 1
	Opal (112°) 5	m 4	3.000K (128 lm/W) - 40W/m 3	Dali 2	☐ Black (9005) 2
		1.410m 5	4.000K (136 lm/W) - 40W/m 4	Push 3	☐ Gray (9006) 3
		m 6	5.000K (136 lm/W) - 40W/m 5	Casambi 5	☒ Matt Gold 4
		1.690m 7	2.700-5.500K (105 lm/W) - 9	Tuya 7	☒ Corten 7
		m	40W/m		☒ Copper Electrolytic Plating C
		1.970m			☐ Custom RAL
		m			
		2.530m			
		m			

Code: **6** ☐ ☐ ☐ ☐ ☐ ☐

Consult delivery terms and conditions.

*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Accessories

End caps 40721 40722 40723	Joint 180° 40220	Joint 90° 40550	Wall bracket 40851 40852 40853	Trimless 40669	Base 3x0,75 (2,5m) Ø60x28mm 40881 40882 40883	Base 5x0,5 (2,5m) Ø60x28mm 40991 40992 40993	Ceiling suspension 40780	Suspension Kit 40790 (2m)



Accessories pages 158-159.



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be