

Venus

This 10W luminaire generates 900 lumens with a high CRI (>90), utilizing Dim-to-Warm COB technology. It offers versatile beam angles (24°, 36°, 50°) and multiple dimming compatibility for precise lighting control.

PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux DtW
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including phase cut dimmable driver
COLORS (Δ)	○ 3 = RAL 9003 ● white 5 = RAL 9005 black
BEAM ANGLE	24° 9005 black
ADJUSTABLE	Rotating 350°, 55° tiltable
DIMMABLE	Yes
SIZE	Ø59 X 152 X 35mm



OPTIONS


OPTIONAL BEAM ANGLE	36°	Art. no.: 3066.010.36.0
	50°	Art. no.: 3066.010.50.0
ANTI-GLARE RING	Black	Included
	Gold	Art. no.: 3066.030.00.9
HONEYCOMB	Art. no.: 3066.040.00.0	
DRIVER OPTIONS	1/10V	250mA 8-11W Art. no.: 0115.250.30.1
	DALI	250mA 8-10W Art. no.: 0110.250.40.1

INFORMATION


Also available in track and recessed version.

⚠ Full warranty only applies when fixture is purchased in

Design Patent Certificate
No. ZL 2019 3 0427875.3 Surface Mount Venus Patent



ANTI-GLARE RING



HONEYCOMB



Honeycomb

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5066.125.24.Δ	DtW	Bridgelux	900lm	10W	90lm/W	1800-3000K DtW	>90	50.000 Hrs	250mA

Δ See colors

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be