

Venus Duo

Featuring two 10W Bridgelux COB units, this luminaire delivers 1,800 total lumens with a CRI >90. It supports Dim-to-Warm technology, various beam angles, and multiple dimming protocols for optimized control.

PRODUCT MATERIAL	Die-cast aluminium	   
LIGHT SOURCE	Bridgelux DtW	
MODULE LIFETIME	Approx. 50.000 hours	
DRIVER	Including phase cut dimmable driver	
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black	
BEAM ANGLE	 24°	
ADJUSTABLE	Rotating 350°, 55° tiltable	
DIMMABLE	Yes	
SIZE	Ø59 X 292 X 36mm	

OPTIONS


OPTIONAL BEAM ANGLE	 36°	Art. no.: 2 X 3066.010.36.0
	 50°	Art. no.: 2 X 3066.010.50.0
ANTI-GLARE RING	Black	Included
	Gold	Art. no.: 2 X 3066.030.00.9
HONEYCOMB	Art. no.: 2 X 3066.040.00.0	
DRIVER OPTIONS	DALI	500mA 12-20W Art. no.: 0120.500.40.2

INFORMATION


Also available in track and recessed version.

 Full warranty only applies when fixture is purchased in

 Design Patent Certificate
No. ZL 2019 3 0427875.3 Surface Mount Venus Patent



ANTI-GLARE RING



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA	HONEYCOMB
Δ See colors										
5068.125.24.Δ	DtW	Bridgelux	2 X 900lm	2 X 10W	90lm/W	1800-3000K 	>90	50.000 Hrs	500mA	

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be