

ZERO IN XL

Suspended LED ring luminaire with 37W, 65W, or 94W power, CRI ≥ 90 , IP20 protection, 100° beam angle, 50,000-hour lifetime, and advanced dimming options.

Zero in XL



Control accessories pages 294-307.

*Finished luminaire. Includes power supply, suspension kit and power cable.

Technical Information

Power	37W / 65W / 94W
Lumens	2.220 lm - 15.040 lm
Installation	Pendant
Material	Aluminium
PCB	Flex (Fine 30)

Code	Di user (Angle)	Size	CCT (lm/W)	Driver	Colour
Code 9	Opal (100°)	1		On / O	1
		400mm	2.700K (150 lm/W)	2	○ White (9003)
		700mm	3.000K (155 lm/W)	3	● Black (9005)
		1.000m	4.000K (160 lm/W) RGB-	Push	○ ● Matt Gold
		m	Im/W) 2.700-	Casambi	○ ● Silver
			5.500K (100 lm/W)	Tuya	○ ● Custom RAL
					9

Code: **9** **1**



ⓘ Consult delivery terms and conditions.

*Create your code according to your preferences. RGB-W and CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be