

Bento Standard 6 Leds Trim

An architectural-grade linear recessed downlight luminaire engineered with six integrated high-performance LEDs and individual microreflectors. Delivering 12.2W of power with an efficacy of up to 115.1 lm/W and CRI 90+, it produces exceptional visual comfort with minimal glare (low UGR). Designed for a 40x168 mm cutout with a trimmed frame, it utilizes a remote driver architecture supporting versatile CCTs (2700K/3000K/4000K) and dimming protocols (DALI/Push) for high-end commercial, corporate, and residential lighting installations.

Technical features

Luminaire total power: 12.7W

Ward Number: 138

Hand length: 109

Correlated Colour Temperature (CCT): 3000K

Lens / reflector angle: FLOOD 47°

LCR: 0.10

Structure material: Aluminium, Polycarbonate

Structure finish: Black

Equipment necessary, but not included

Voltage / frequency: 18VDC / max. 700mA

Useful life: 50,000h L80B20

Warranty: 5 years



Luminotechnic features

Luminance Coefficients: 98


Luminance (cd/m²): 63

0781-902

Hugo Acharya et al.: 3

Photobiological risk: R(60)

Lamp		Lamp/box	Quantity	Light intensity power (W)	Correlated Color Temperature (K)
Coating /wavelength	Watt				
Working Plane	0.2				
Beam dimensions	2x104, 1x104				
Lamp connector	12.5				
Lamp length	14.8				



Logistics



Net weight (g): 0.21

Packaged weight (kg): 0.26

Packaging: 60mmx55mm x 185mm

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be