

Krizia P/G

An indoor surface-mounted ceiling luminaire engineered with high-performance integrated LED modules within a robust, precision-crafted metal structure. Featuring an opal white acrylic diffuser, it guarantees wide-angle light distribution with minimal glare and smooth luminance. Powered by an integrated electronic driver, the fixture offers stable thermal management, high color rendering, and adjustable CCT options (3000K/4000K) tailored for large residential, hospitality, and commercial architectural spaces.



KRIZIA P/G

FKRPBE3-NEW-BEIGE

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led integrato

Power: 50W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 4000lm-4100lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Diretta

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: E

Volume: 0,0321m3

Gross Weight: 4.70 Kg

Net Weight: 3.28 Kg

Struttura in alluminio. Finitura in new beige. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. New beige finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en nouveau beige. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in New Beige. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

Krizia P/G

An indoor surface-mounted ceiling luminaire engineered with high-performance integrated LED modules within a robust, precision-crafted metal structure. Featuring an opal white acrylic diffuser, it guarantees wide-angle light distribution with minimal glare and smooth luminance. Powered by an integrated electronic driver, the fixture offers stable thermal management, high color rendering, and adjustable CCT options (3000K/4000K) tailored for large residential, hospitality, and commercial architectural spaces.



KRIZIA P/G

FKRPTE3-TERRACOTTA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led integrato

Power: 50W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 4000lm-4100lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Diretta

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: E

Volume: 0,0321m3

Gross Weight: 4.70 Kg

Net Weight: 3.28 Kg

Struttura in alluminio. Finitura in terracotta. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Terracotta finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en terre cuite. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Terrakotta. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

Krizia P/G

An indoor surface-mounted ceiling luminaire engineered with high-performance integrated LED modules within a robust, precision-crafted metal structure. Featuring an opal white acrylic diffuser, it guarantees wide-angle light distribution with minimal glare and smooth luminance. Powered by an integrated electronic driver, the fixture offers stable thermal management, high color rendering, and adjustable CCT options (3000K/4000K) tailored for large residential, hospitality, and commercial architectural spaces.



KRIZIA P/G FKRPV3-VERDE-SALVIA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto
Source: Led integrato
Power: 50W
Power Supply: 220-240V AC _ 50/60Hz
Dimming: Dimmerabile _ taglio fase+push non incl.
Lumen: 4000lm-4100lm
Color Temperature: 3000K-4000K
Light Beam: 120° _ Diretta
CRI: >80
Lifespan: 30.000h
IP Rating: IP20
Insulation Class: I
Energy Class: E
Volume: 0,0321m3
Gross Weight: 4.70 Kg
Net Weight: 3.28 Kg

Struttura in alluminio. Finitura in verde salvia. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Sage green finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en vert sauge. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Salbeigrün. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be