

Krizia P/P

A surface-mounted indoor ceiling luminaire featuring high-performance integrated LED modules housed within a precision-crafted aluminum structure. Equipped with an opal white acrylic diffuser, it ensures wide-angle, homogeneous light distribution with reduced glare. Operating with an integrated electronic driver, the fixture supports high color rendering, reliable thermal dissipation, and dual CCT options (3000K/4000K) suitable for refined architectural, commercial, or residential interior environments.



TECHNICAL DATA

Installation: Interno _ Lampada a soffitto
Source: Led integrato
Power: 30W
Power Supply: 220-240V AC _ 50/60Hz
Dimming: Dimmerabile _ taglio fase+push non incl.
Lumen: 2500lm-2600lm
Color Temperature: 3000K-4000K
Light Beam: 120° _ Diretta
CRI: >80
Lifespan: 30.000h
IP Rating: IP20
Insulation Class: I
Energy Class: E
Volume: 0,0146m³
Gross Weight: 2.49 Kg
Net Weight: 1.67 Kg

Struttura in alluminio. Finitura in new beige. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. New beige finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en nouveau beige. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in New Beige. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

Krizia P/P

A surface-mounted indoor ceiling luminaire featuring high-performance integrated LED modules housed within a precision-crafted aluminum structure. Equipped with an opal white acrylic diffuser, it ensures wide-angle, homogeneous light distribution with reduced glare. Operating with an integrated electronic driver, the fixture supports high color rendering, reliable thermal dissipation, and dual CCT options (3000K/4000K) suitable for refined architectural, commercial, or residential interior environments.



KRIZIA P/P

FKRPTE1-TERRACOTTA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto
Source: Led integrato
Power: 30W
Power Supply: 220-240V AC _ 50/60Hz
Dimming: Dimmerabile _ taglio fase+push non incl.
Lumen: 2500lm-2600lm
Color Temperature: 3000K-4000K
Light Beam: 120° _ Diretta
CRI: >80
Lifespan: 30.000h
IP Rating: IP20
Insulation Class: I
Energy Class: E
Volume: 0,0146m³
Gross Weight: 2.49 Kg
Net Weight: 1.67 Kg

Struttura in alluminio. Finitura in terracotta. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Terracotta finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en terre cuite. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Terrakotta. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

Krizia P/P

A surface-mounted indoor ceiling luminaire featuring high-performance integrated LED modules housed within a precision-crafted aluminum structure. Equipped with an opal white acrylic diffuser, it ensures wide-angle, homogeneous light distribution with reduced glare. Operating with an integrated electronic driver, the fixture supports high color rendering, reliable thermal dissipation, and dual CCT options (3000K/4000K) suitable for refined architectural, commercial, or residential interior environments.



KRIZIA P/P

FKRPV1-VERDE-SALVIA

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto
Source: Led integrato
Power: 30W
Power Supply: 220-240V AC _ 50/60Hz
Dimming: Dimmerabile _ taglio fase+push non incl.
Lumen: 2500lm-2600lm
Color Temperature: 3000K-4000K
Light Beam: 120° _ Diretta
CRI: >80
Lifespan: 30.000h
IP Rating: IP20
Insulation Class: I
Energy Class: E
Volume: 0,0146m3
Gross Weight: 2.49 Kg
Net Weight: 1.67 Kg

Struttura in alluminio. Finitura in verde salvia. Diffusore in acrilico bianco opale. Sorgente luminosa led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi). Dimmer compatibile (GDI002).

Aluminium frame. Sage green finish. Opal white acrylic diffuser. Phase-cut dimmable LED light source via external dimmer+push (not included). Matching dimmer (GDI002).

Cadre en aluminium. Finition en vert sauge. Diffuseur acrylique blanc opale. Source lumineuse LED à gradation de phase via un gradateur externe+poussoir (non inclus). Variateur compatible (GDI002).

Rahmen aus Aluminium. Ausführung in Salbeigrün. Opalweißer Acryldiffusor. Phasenanschnitt dimmbare LED-Lichtquelle über externen Dimmer+Druck (nicht im Lieferumfang enthalten). Kompatibler Dimmer (GDI002).

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be