

ZERO-IN

An architectural suspended circular luminaire made of a slender extruded aluminum profile available in Ø400 mm, Ø700 mm, Ø1000 mm, and Ø1500 mm formats. Designed with an inward-facing high-efficiency integrated LED source and an opal diffuser, it delivers 26W to 96W of power with outputs up to 6,912 lumens at a 100° beam angle and CRI >80. The IP20-rated system supports static color temperatures (2700K, 3000K, 4000K), RGBW, and Tunable White (2700–5500K), operating via On/Off, DALI, Push, Casambi, or Tuya Smart control protocols for custom interior environments.


Zero In

ZEROINØ400 26W OPAL 100° ON/OFF 2700K WHITE

Reference 122211

Category Custom lighting

PRODUCT	
Housing material	ALUMINUM
Colour / Finishes	MATT WHITE
Custom RAL	Yes
Power (W)	26 W
Luminous flux (lm)	1950
Efficacy (lm/W)	75
Beam angle (°)	100
LIGHT SOURCE	
LED type	SMD
Colour temperature (K)	2700K
Chromatic stability (SDCM)	SDCM3
UGR	>22
Protection (IP)	IP20
Protection (IK)	IK04
Power factor	>0,9
Lifespan (h)	50000
Warranty (years)	5
Energy label	G
Control	ON/OFF
ELECTRICAL DATA	
Input voltage	220/240
Maximum current (A)	0,12
Frequency (Hz)	50/60Hz
Insulation class	CLASS I
Size	Ø400
MOUNTING DATA	
Item weight (kg)	0.4
Total weight (kg)	0
Packaging unit	1



Disclaimer
Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

ZERO-IN

An architectural suspended circular luminaire made of a slender extruded aluminum profile available in Ø400 mm, Ø700 mm, Ø1000 mm, and Ø1500 mm formats. Designed with an inward-facing high-efficiency integrated LED source and an opal diffuser, it delivers 26W to 96W of power with outputs up to 6,912 lumens at a 100° beam angle and CRI >80. The IP20-rated system supports static color temperatures (2700K, 3000K, 4000K), RGBW, and Tunable White (2700–5500K), operating via On/Off, DALI, Push, Casambi, or Tuya Smart control protocols for custom interior environments.

Zero In

ZEROINØ400 26W OPAL 100° ON/OFF 2700K BLACK

Reference 122212

Category Custom lighting

PRODUCT

Housing material	ALUMINUM
Colour / Finishes	MATT BLACK
Custom RAL	Yes
Power (W)	26 W
Luminous flux (lm)	1950
Efficacy (lm/W)	75
Beam angle (°)	100





LIGHT SOURCE

LED type	SMD
Colour temperature (K)	2700K
Chromatic stability (SDCM)	SDCM3
UGR	>22
Protection (IP)	IP20
Protection (IK)	IK04
Power factor	>0,9
Lifespan (h)	50000
Warranty (years)	5
Energy label	G
Control	ON/OFF



ELECTRICAL DATA

Input voltage	220/240
Maximum current (A)	0,12
Frequency (Hz)	50/60Hz
Insulation class	CLASS I
Size	Ø400



MOUNTING DATA

Item weight (kg)	0.4
Total weight (kg)	0
Packaging unit	1

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

ZERO-IN

An architectural suspended circular luminaire made of a slender extruded aluminum profile available in Ø400 mm, Ø700 mm, Ø1000 mm, and Ø1500 mm formats. Designed with an inward-facing high-efficiency integrated LED source and an opal diffuser, it delivers 26W to 96W of power with outputs up to 6,912 lumens at a 100° beam angle and CRI >80. The IP20-rated system supports static color temperatures (2700K, 3000K, 4000K), RGBW, and Tunable White (2700–5500K), operating via On/Off, DALI, Push, Casambi, or Tuya Smart control protocols for custom interior environments.

Zero In

ZEROINØ400 26W OPAL 100° ON/OFF 2700K GOLD

Reference 122214

Category Custom lighting

PRODUCT	
Housing material	ALUMINUM
Colour / Finishes	MATT GOLD
Custom RAL	Yes
Power (W)	26 W
Luminous flux (lm)	1950
Efficacy (lm/W)	75
Beam angle (°)	100
LIGHT SOURCE	
LED type	SMD
Colour temperature (K)	2700K
Chromatic stability (SDCM)	SDCM3
UGR	>22
Protection (IP)	IP20
Protection (IK)	IK04
Power factor	>0,9
Lifespan (h)	50000
Warranty (years)	5
Energy label	G
Control	ON/OFF
ELECTRICAL DATA	
Input voltage	220/240
Maximum current (A)	0,12
Frequency (Hz)	50/60Hz
Insulation class	CLASS I
Size	Ø400
MOUNTING DATA	
Item weight (kg)	0.4
Total weight (kg)	0
Packaging unit	1



Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be

ZERO-IN

An architectural suspended circular luminaire made of a slender extruded aluminum profile available in Ø400 mm, Ø700 mm, Ø1000 mm, and Ø1500 mm formats. Designed with an inward-facing high-efficiency integrated LED source and an opal diffuser, it delivers 26W to 96W of power with outputs up to 6,912 lumens at a 100° beam angle and CRI >80. The IP20-rated system supports static color temperatures (2700K, 3000K, 4000K), RGBW, and Tunable White (2700–5500K), operating via On/Off, DALI, Push, Casambi, or Tuya Smart control protocols for custom interior environments.

Zero In

ZEROINØ400 26W OPAL 100° ON/OFF 2700K GOLD

Reference 122214

Category Custom lighting

PRODUCT

Housing material	ALUMINUM
Colour / Finishes	MATT GOLD
Custom RAL	Yes
Power (W)	26 W
Luminous flux (lm)	1950
Efficacy (lm/W)	75
Beam angle (°)	100




LIGHT SOURCE

LED type	SMD
Colour temperature (K)	2700K
Chromatic stability (SDCM)	SDCM3
UGR	>22
Protection (IP)	IP20
Protection (IK)	IK04
Power factor	>0,9
Lifespan (h)	50000
Warranty (years)	5
Energy label	G
Control	ON/OFF



ELECTRICAL DATA

Input voltage	220/240
Maximum current (A)	0,12
Frequency (Hz)	50/60Hz
Insulation class	CLASS I
Size	Ø400



MOUNTING DATA

Item weight (kg)	0.4
Total weight (kg)	0
Packaging unit	1

Disclaimer

Alle technische gegevens, evenals gewichts- en afmetingsspecificaties, zijn gebaseerd op standaardwaarden. Wij behouden ons het recht om technische wijzigingen aan te brengen. Productafbeeldingen dienen ter illustratie en kunnen afwijken van het origineel.

FL

www.formaluna.be